

BOC PP (PES) Pleated Filter Cartridge

折叠滤芯



技术参数

Technical Data

滤芯尺寸/Cartridge Dimensions

外径/Outer Diameter 2.5" (63mm), 2.7" (69mm)

长度/Length 5", 9.75", 9.87", 10", 20", 30", 40", 60", 70"

部件材质/Parts List

滤材/Filtering Material 聚丙烯, 聚醚砜/Polypropylene (PP), PES

支撑/导流层/外壳/中心杆/端盖
Support/ Guide Layer/ Shell/ Center Rod/ End Cover 聚丙烯, 聚醚砜/Polypropylene (PP), PES

密封圈材质/Sealing Ring Material 硅橡胶, 乙丙橡胶, 丁腈橡胶, 氟橡胶, 特氟龙, FEP包裹Viton/
Silicone Rubber, EPDM, NBR, Fluororubber, Teflon, FEP-wrapped Viton

滤芯性能/Cartridge Performance

过滤精度/Filtration Grade 0.1µm, 0.22µm, 0.45µm, 1µm, 3µm, 5µm, 10µm, 20µm, 50µm

最高操作温度/Maximum Working Temperature 1.0Bar 80°C, 当温度超过50°C时推荐更换内部支撑圈/
1.0 Bar at 80°C, it is recommended to replace the inner supporting ring when the temperature exceeds 50°C

最大压差/Maximum Differential Pressure 4.0Bar在常温下/At room temperature

消毒温度时间/Sterilization Temperature And Time 121°C, 每次30分钟/30 minutes at 121°C